# **EXECUTIVE 71CM**



FLUX CORED WIRE TECHNICAL DATA SHEET



#### DESCRIPTION

Executive 71CM carbon steel flux cored wire is designed to increase total productivity while reducing your total welding costs.

Executive 71CM is specially designed to reduce wear on consumables and produce great clean welds that require minimal cleanup. This is all to help improve arc on time to keep you welding.

Executive 71CM is an easy to use wire that offers low fume generation, minimal spatter levels, and an easy to remove slag.

Executive 71CM wire is easy to weld with very smooth arc characteristics allowing for great operator appeal. Executive 71CM is a very consistent wire that produces an excellent bead profile and strong mechanical properties.

## **APPLICATIONS & FEATURES**

Typical applications include structural steel welding, pressure vessels, bridges, transportation equipment, as well as all general fabrication where high productivity and good mechanical properties are required.

Certified material test reports with actual chemistry and actual mechanicals for both 100%  $CO_2$  and 75% Ar / 25%  $CO_2$  shielding gases are provided with each heat/lot.

#### **TYPICAL WIRE CHEMISTRY & MECHANICAL PROPERTIES**

С	Si	Mn	Р	S	Cu	Ni	Cr	Мо	V
0.05	0.57	1.44	0.014	0.007	0.01	0.01	0.02	0.001	0.02
Tensile Strength: Yield Strength:		83,500 PSI min 72,600 PSI min		Diffusible Hydrogen: Elongation:		3.86 ml/10 31%	•	arpy Impact diographic T	: 76 ft-lb (103 J) at -4°F (-20°C) est: Acceptable

#### **TYPICAL WELDING PARAMETERS**

Diameter	Voltage	Amperage	Wire Feed Speed (in./min)	Stick-Out	Flow Rate (SCFH)	Shielding Gas*
	21-24	140	205		(SCFH)	
.045"	23-26	200	340	3/4"	40-50	75% Ar / 25% CO <sub>2</sub>
	26-29	240	430			, -
	22-25	160	145			
.052"	24-27	220	235	3/4" - 1"	40-50	75% Ar / 25% CO <sub>2</sub>
	27-30	280	345			
	23-26	200	120			
.062"	24-27	260	190	3/4" - 1"	40-50	75% Ar / 25% CO <sub>2</sub>
	27-30	320	270			

\*If using 100% CO<sub>2</sub>, increase by 2 volts.

### **STANDARD PACKAGING**

Spools

44-lb plastic spools

2,640-lb pallet

# CLASSIFICATION

AWS A5.20/ASME SFA A5.20 Class E71T-1C/1M-9C/9M H8 AWS A5.36/ASME SFA A5.36 Class E71T1/9-C1A2-CS1-H8 AWS A 5.36/ASME SFA A5.36 Class E71T1/9-M21A2-CS1-H8 CWB E491T1-C1A2-CS1-H8 (E491T-1-H8) & E491T1-M21A2-CS1-H8 (E491T-1M-H8)

